

COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR

1	Manufacturer: Atlas Copco														
2	Model Number: ZR 250 VSD-8.6	Date: 01-06-2024													
	<input type="checkbox"/> Air-cooled <input checked="" type="checkbox"/> Water-cooled	Type: Screw													
	<input type="checkbox"/> Lubricated <input checked="" type="checkbox"/> Oil-free	# of Stages: 2													
3	Full Load Operating Pressure*(b)	124.7	psig*(b)												
4	Drive Motor Nominal Rating	335.3	hp												
5	Drive Motor Nominal Efficiency	95.2	percent												
6	Fan Motor Nominal Rating (if applicable)	--	hp												
7	Fan Motor Nominal Efficiency	--	percent												
8*	Input Power (kW)	Capacity (acfm) *(a,d)	Specific Power (kW/100 acfm)*(d)												
	269.6 Max	1,399.1	19.3												
	225.6	1,177.5	19.2												
	185.4	955.9	19.4												
	148.1	734.3	20.2												
	112.8 Min	512.7	22.0												
9*	Total Package Input Power at Zero Flow*(c,d)	20.8	kW												
10	<table border="1"> <caption>Graph Data: Specific Power vs Capacity</caption> <thead> <tr> <th>Capacity (ACFM)</th> <th>Specific Power (kW/100ACFM)</th> </tr> </thead> <tbody> <tr> <td>500</td> <td>22.5</td> </tr> <tr> <td>750</td> <td>20.2</td> </tr> <tr> <td>950</td> <td>19.4</td> </tr> <tr> <td>1200</td> <td>19.2</td> </tr> <tr> <td>1400</td> <td>19.3</td> </tr> </tbody> </table>			Capacity (ACFM)	Specific Power (kW/100ACFM)	500	22.5	750	20.2	950	19.4	1200	19.2	1400	19.3
Capacity (ACFM)	Specific Power (kW/100ACFM)														
500	22.5														
750	20.2														
950	19.4														
1200	19.2														
1400	19.3														

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

Notes:

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- Tolerance is specified in ISO 1217, Annex E, as shown in table below:
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member



Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ / min	ft ³ / min	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	+/- 10
0.5 to 1.5	15 to 50	+/- 6	+/- 7	
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	