

COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR

1	Manufacturer: Atlas Copco														
2	Model Number: ZT 75 VSD STD-10.4	Date:	01-06-2024												
	<input checked="" type="checkbox"/> Air-cooled <input type="checkbox"/> Water-cooled	Type:	Screw												
	<input type="checkbox"/> Lubricated <input checked="" type="checkbox"/> Oil-free	# of Stages:	2												
3	Full Load Operating Pressure*(b)	150.0	psig*(b)												
4	Drive Motor Nominal Rating	100.6	hp												
5	Drive Motor Nominal Efficiency	93.6	percent												
6	Fan Motor Nominal Rating (if applicable)	8.9	hp												
7	Fan Motor Nominal Efficiency	91.7	percent												
8*	Input Power (kW)	Capacity (acfm) *(a,d)	Specific Power (kW/100 acfm)*(d)												
	91.4 Max	385.7	23.7												
	81.1	330.5	24.5												
	71.2	275.2	25.9												
	61.8	220.0	28.1												
	52.9 Min	164.8	32.1												
9*	Total Package Input Power at Zero Flow*(c,d)	14.5	kW												
10	<table border="1"> <caption>Graph Data Points</caption> <thead> <tr> <th>Capacity (ACFM)</th> <th>Specific Power (kW/100ACFM)</th> </tr> </thead> <tbody> <tr> <td>164.8</td> <td>32.1</td> </tr> <tr> <td>220.0</td> <td>28.1</td> </tr> <tr> <td>275.2</td> <td>25.9</td> </tr> <tr> <td>330.5</td> <td>24.5</td> </tr> <tr> <td>385.7</td> <td>23.7</td> </tr> </tbody> </table>			Capacity (ACFM)	Specific Power (kW/100ACFM)	164.8	32.1	220.0	28.1	275.2	25.9	330.5	24.5	385.7	23.7
Capacity (ACFM)	Specific Power (kW/100ACFM)														
164.8	32.1														
220.0	28.1														
275.2	25.9														
330.5	24.5														
385.7	23.7														

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

Notes:

- Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.
- The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- Tolerance is specified in ISO 1217, Annex E, as shown in table below:
NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member



Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ / min	ft ³ / min	%	%	
Below 0.5	Below 15	+/- 7	+/- 8	+/- 10
0.5 to 1.5	15 to 50	+/- 6	+/- 7	
1.5 to 15	50 to 500	+/- 5	+/- 6	
Above 15	Above 500	+/- 4	+/- 5	