

PAS 300 HF T4F

Diesel - Qmax 2,160 m³/h (9,510 USgpm) - Hmax 71 m (233 ft)



Indicative picture of the product

PAS HF - Vacuum prime centrifugal pumps

The pump system consists of a centrifugal pump and a separator, which enables air to be separated from the liquid and be sucked by a vacuum pump - making automatic priming possible. Even with suction heights of several meters the machine rapidly evacuates the air from the suction pipe and starts to pump. Additionally, thanks to the semi-open impeller, the PAS HF range is also suitable for pumping liquids with solids in suspension.

Applications

Both Atlas Copco and Varisco have decades of experience in designing and producing pumps. We have put those years of expertise into providing a solutions portfolio that works across multiple applications. The PAS HF (high flow) range is packed with features that not only meet, but exceed the needs of the market. We are focused on an efficient, extremely versatile pump that is suitable for many industries, including construction, general dewatering and emergency applications, such as flood clean up.

Benefits

Pump

High efficiency: 72% (B.E.P)

Rapid "dry" priming

Up to a height of 7,5 m (24.6 ft)

High resistance

To abrasive liquids and turbid sandy waters

Semi-open impeller

Solids handling up to 89 mm (3.5")

Diaphragm vacuum pump

Oil free suitable for dry running: no contamination of the environment

Mechanical shaft seal in oil bath

It allows the "dry running" operation of the pump

PAS 300 HF T4F

Performance curves


Test according to UNI EN ISO 9906 standard - level 2

Test liquid: clean water, density 1,000 kg/m³

Spherical solids handling: D.89 mm (3.5")

Priming time: 30 s from 1,5 m (4.9 ft)

Max absorbed power: 195,0 kW - 261.5 HP (1.600 rpm)



PAS 300 HF T4F

Technical data

Pump

Model	PAS 300HF
Qmax	2.160 m ³ /h - 36.000 l/min (9,510 USgpm)
Hmax	71 m (233 ft)
Q max eff.	1.580 m ³ /h - 26.330 l/min (6,960 USgpm)
Eff. max	72 %
Suction port	Flanged - ANSI 300
Delivery port	Flanged - ANSI 300
Impeller type	Semi-Open, 2 vane
Solids handling	89 mm (3.5 ")
Material	G11
Casing	ASTM A536 ductile iron
Impeller	ASTM A536 ductile iron
Wear plates	ASTM A48 Class 20 cast iron
Number of plates	1
Shaft	AISI 630 stainless steel
Mechanical seal	Silicon carbide / Tungsten carbide
Elastomers	VITON

Priming system

Vacuum pump	V22
Vacuum pump type	Diaphragm
Nominal air capacity	85 m ³ /h (50.0 cfm)
Max vacuum	0,9 bar (13.1 psi - 26.6 inHg)
Separator type	-
Separator material	EN-GJL-200 cast iron
Drives	Link belt

Engines

Make	Volvo			
Model	TAD872VE			
Type	Diesel turbo common rail			
Displacement	7.700 cm ³ (470 in ³)			
No. cylinders	6			
Cooling	Liquid with radiator			
Rpm type	Variable			
Standard speed	1.600 rpm			
US emissions	EPA Tier 4F			
Starting	Electric			
Starting voltage	24 V			
Oil change interval	500 h			
Speed [rpm]	1000	1200	1400	1600
Power [kW]*	112,8	155,1	183,3	206,8
Power [HP]	151.2	207.9	245.7	277.2

* continuous power ISO 3046 ICXN

Control panel

Model	PW 750
	Manual operation
	Automatic operation: start-stop with transducers or floats
	Digital display with 6 languages (EN, SV, FR, DE, ES, IT) with:
	Hour meter, Rev counter, Liquid temperature, Oil pressure and temperature
	Battery voltmeter, Fuel level (%) and consumption (l/h)
	Engine control unit (ECU) commands shutdown, derate or run depending on operating anomalies
	Automatic engine shutdown in case of:
	- low oil pressure
	- engine overheating
	- low battery voltage
	(engine failure alarms with LED lights and display message)
	Service time (hours)
	Push-button accelerator (up/down)
	(PW1 FleetLink control as option)

PAS 300 HF T4F

Arrangement

Technical data	
Material	ASTM A36 steel
Coatings	Epoxy powder, average thickness of 3 MIL
Battery	Acid charge Pb-Ca maintenance free, 12 V - 100 Ah - 400 A
Tank	450 l (119 USG)
Drip pan	495 l (131 USG) (110% of the total volume of the tank)
Locking keys	Control panel door and canopy doors
Noise level	67-72 dB(A) @10 m (32 ft)
Fuel consumption	10 US Gal/hr @1600 rpm @BEP

PAS 300HF CNP



Dimensions	2220 x 3970 x 2000 mm (87 x 156 x 79 ")
H suction port	0,7 m (2.3 ft)
Dry weight	4300 kg (9,480 lb)

PAS 300HF SKID



Dimensions	1940 x 3250 x 2155 mm 76 x 128 x 85 "
H suction port	0,7 m (2.3 ft)
Dry weight	3700 kg (8,160 lb)